

CA24N

2 1

-37A23

ONTARIO ASSOCIATION OF MOTOR COACH OPERATORS

BRIEF SUBMITTED TO

THE ROYAL COMMISSION TO INQUIRE
INTO HIGHWAY TRANSPORTATION
IN THE
PROVINCE OF ONTARIO

EXHIBIT X

SCHEDULE OF STANDARD SINGLE
AND RETURN FARES IN EFFECT
ON TYPICAL ROUTES IN THE
PROVINCE OF ONTARIO

TYPICAL MOTOR COACH FARES

Between		Miles O.W.	Single Fare \$	Cents Per Mile	Return Fare \$	Cents Per Mile
Toronto	North Bay	223.1	6.10	2.7	11.00	2.5
"	Huntsville	142.1	3.95	2.8	7.15	2.5
"	Orillia	82.4	2.25	2.7	4.05	2.4
"	Barrie	58.6	1.65	2.8	3.00	2.5
"	Newmarket	30.2	.90	3.0	1.65	2.7
"	Sutton	51.9	1.60	3.1	2.90	2.8
"	Markham	22.4	.60	2.7	1.10	2.5
"	Oshawa	32.4	.85	2.6	1.55	2.4
"	Whitby	28.5	.70	2.5	1.30	2.3
"	Midland	90.6	2.65	2.9	4.80	2.6
"	Alliston	57.0	1.50	2.6	2.70	2.4
"	Guelph	59.4	1.20	2.0	2.20	1.9
"	Owen Sound	145.7	3.40	2.3	6.15	2.1
"	Kitchener	74.9	1.60	2.1	2.90	1.9
"	London	142.0	2.90	2.0	5.25	1.8
"	Chatham	210.7	4.25	2.0	7.65	1.8
"	Windsor	266.5	5.10	1.9	9.20	1.7
"	Hamilton	43.7	1.00	2.3	1.80	2.1
"	Grimsby	53.4	1.40	2.6	2.55	2.4
"	Niagara Falls	85.7	2.25	2.6	4.05	2.4
"	Fort Erie	104.8	2.80	2.7	5.05	2.4
"	Brockville	218.0	4.75	2.2	8.55	2.0
"	Kingston	167.4	4.00	2.4	7.20	2.1
"	Ottawa	293.0	5.90	2.0	10.65	1.8
"	Goderich	147.1	3.45	2.3	6.25	2.1
"	Sarnia	209.0	4.30	2.1	7.75	1.9
Hamilton	Niagara Falls	49.6	1.40	2.8	2.55	2.6
"	Grimsby	16.7	.50	3.0	.90	2.7
"	Beamsville	21.7	.60	2.8	1.10	2.5
"	Fort Erie	69.0	2.00	2.9	3.60	2.6
"	London	79.5	2.00	2.5	3.60	2.3
"	Windsor	199.5	4.75	2.4	8.25	2.1
"	Jarvis	28.9	.85	2.9	1.55	2.7
"	Brantford	22.9	.65	2.8	1.20	2.6
"	Milton	24.8	.75	3.0	1.35	2.7

TYPICAL MOTOR COACH TABLE

Between	Miles O.W.	Single Rate ¢	Coach Rate ¢	Return Rate ¢	Coach Rate ¢
Toronto	92.1	1.10	2.7	11.00	2.5
"	142.1	2.95	3.8	7.15	2.5
"	82.4	2.95	2.7	4.05	2.4
"	58.6	1.95	2.8	2.00	2.5
"	30.2	1.90	2.0	1.65	2.7
"	21.2	1.80	2.1	2.90	2.8
"	22.4	.60	2.1	1.10	2.3
"	32.4	.85	2.6	1.55	2.4
"	38.2	.70	2.5	1.30	2.4
"	40.8	2.65	2.9	4.80	2.6
"	27.0	1.20	2.6	2.70	2.4
"	22.4	1.20	2.0	2.20	1.9
"	122.7	3.40	2.9	6.15	2.1
"	74.9	1.80	2.1	2.90	1.9
"	122.0	2.90	2.0	5.25	1.8
"	210.7	4.25	2.0	7.25	1.8
"	222.2	2.10	1.9	3.80	1.7
"	42.7	1.00	2.2	1.80	2.1
"	22.4	1.40	2.2	2.25	2.2
"	22.7	2.25	2.6	4.05	2.4
"	104.8	2.80	2.7	5.05	2.4
"	218.0	4.75	2.2	8.25	2.0
"	127.4	4.00	2.4	7.20	2.1
"	222.0	2.90	2.0	10.25	1.8
"	147.1	2.45	2.5	6.25	2.1
"	202.0	4.30	2.1	7.75	1.8
"	42.6	1.40	2.2	2.25	2.2
"	16.7	.50	2.0	.90	2.7
"	21.7	.60	2.8	4.10	2.5
"	22.0	2.00	2.9	3.60	2.6
"	72.5	2.00	2.2	4.60	2.3
"	122.2	4.75	2.4	6.25	2.1
"	22.2	.85	2.2	1.55	2.7
"	22.2	.65	2.8	1.20	2.6
"	24.8	.75	2.0	1.35	2.7

